

		Amount of Sight Adjustment Necessary to Correct POI																				
Sight Radius>	14"	15"	16"	17"	18"	19"	20"	21"	22"	23"	24"	25"	26"	27"	28"	29"	30"	31"	32"	33"	34"	
Needed Correction at Target +/-	*1"	0.0038	0.0041	0.0044	0.0047	0.005	0.0053	0.0055	0.0058	0.0061	0.0064	0.0066	0.0069	0.0072	0.0074	0.0077	0.008	0.0082	0.0085	0.0088	0.0091	0.0093
	*2"	0.0078	0.0083	0.0089	0.0094	0.01	0.0105	0.0111	0.0116	0.0122	0.0127	0.0133	0.0138	0.0144	0.0149	0.0155	0.016	0.0156	0.0171	0.0177	0.0182	0.0188
	*3"	0.0117	0.0125	0.0133	0.0142	0.015	0.0159	0.0167	0.0175	0.0184	0.0192	0.0201	0.0209	0.0217	0.0226	0.0234	0.0243	0.0251	0.0259	0.0268	0.0276	0.0285
	*4"	0.0155	0.0167	0.0178	0.0189	0.02	0.0211	0.0222	0.0234	0.0244	0.0255	0.0266	0.0278	0.0289	0.03	0.0311	0.0322	0.0333	0.0344	0.0355	0.0366	0.0377
	*5"	0.0194	0.0208	0.0222	0.0236	0.025	0.0264	0.0278	0.0292	0.0306	0.0319	0.0333	0.0347	0.0361	0.0375	0.0389	0.0403	0.0417	0.0431	0.0445	0.0458	0.0472
	*6"	0.0233	0.025	0.0267	0.0283	0.03	0.0317	0.0333	0.035	0.0367	0.0384	0.04	0.0417	0.0434	0.045	0.0467	0.0484	0.05	0.0517	0.0534	0.0551	0.0567

*Amount of error at 100 yards is given in inches